

WO 2004/051242

ECT/NL2003/000515

39

Claims

1. Use of an instrument for measuring a Raman signal of tissue, the instrument comprising a laser, a signal detection unit for measuring the Raman signal, and a
5 fiber optic probe, wherein the fiber optic probe comprises one or more optical fibers for directing laser light onto the tissue and for collecting light that is scattered by the tissue and guiding the collected light away from the tissue towards the signal detection unit, the fiber comprising a core, a cladding and optionally a coating, and the fiber or fibers for collecting light having substantially no Raman signal in one
10 or more parts of the 2500-3700 cm^{-1} spectral region, and wherein the detection unit records the Raman signal scattered by the tissue in said spectral region.
2. Use of an instrument according to claim 1, wherein the detection unit does substantially not measure fluorescence generated by other sources than the tissue.
15
3. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises at least one fiber having a low OH⁻ fused silica core.
4. Use of an instrument according to one of the preceding claims, wherein the fiber
20 optic probe comprises at least one optical fiber having a fused silica core and a fused silica or Teflon or TECS cladding.
5. Use of an instrument according to one of the preceding claims, by using a coating material in which intrinsically little or substantially no signal is generated in the
25 2500-3700 cm^{-1} wavenumber interval.
6. Use of an instrument according to one of the preceding claims, wherein the coating of the optical fiber comprises one or more of Teflon coatings and metal coatings.
- 30 7. Use of an instrument according to one of the preceding claims, wherein the detection unit substantially measures only the signal obtainable from the core of the optic fiber.

WO 2004/051242

PCT/NL2003/000815

40

8. Use of an instrument according to one of the preceding claims, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a laser light absorbing material.
- 5
9. Use of an instrument according to one of the preceding claims, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a material having a higher refractive index than the first coating material.
- 10
10. Use of an instrument according to one of the preceding claims, wherein the optical fiber comprises a laser light absorbing end tip coating.
- 15
11. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises an optical fiber that both directs laser light onto the tissue and collects light that is scattered by the tissue and guides the collected light away from the tissue towards the signal detection unit, and wherein the fiber has substantially no Raman signal in one or more parts of the $2500\text{-}3700\text{ cm}^{-1}$ spectral region.
- 20
12. Use of an instrument according to one of the preceding claims, wherein the detection unit records the Raman signal in one or more parts of the $2700\text{-}3100\text{ cm}^{-1}$ spectral region.
- 25
13. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises an optical element at the distal end of the optical fiber.
- 30
14. Use of an instrument according to one of the preceding claims, further comprising a signal analysis unit which analyses the recorded Raman signal, the analysis comprising an algorithm which outputs data regarding the molecular composition of the tissue and/or the clinical diagnostic class to which the tissue belongs.

WO 2004/051242

PCT/NL2003/000815

41

15. Use of an instrument according to one of the preceding claims for analysis and/or diagnosis of atherosclerotic plaque.
- 5 16. Use of an instrument according to one of the preceding claims for use in the analysis and/or diagnosis of cancerous tissue or pre-cancerous tissue.
17. Use of an instrument according to one of the preceding claims for skin diagnosis.
- 10 18. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe is integrated or combined with a catheter.
- 15 19. Use of an instrument according to one of the preceding claims, wherein Raman measurements can be combined with fluorescence and/or near-infrared absorption measurements and wherein the detection unit also comprises a detection unit for measuring the intensity and/or spectrum of tissue fluorescence and/or a detection unit for measuring near-infrared absorption.
- 20 20. Use of an instrument according to claim 19, wherein fluorescence and/or near-infrared absorption measurements make use of a fiber also used in obtaining Raman signal.
- 25 21. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises a bundle of fibers for measuring and/or scanning a tissue area.
22. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises one optical fiber, the fiber having substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
- 30 23. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe is brought in, or in contact with, or in proximity to the tissue under investigation.

BEST AVAILABLE COPY

WO 2004/051242

PCT/NL2003/000815

42

24. Use of an instrument according to one of the preceding claims, wherein the tissue is excised, biopsied or taken from a human or animal body before measuring.
- 5 25. An instrument for measuring a Raman signal of tissue, the instrument comprising a laser, a signal detection unit for measuring the Raman signal, and a fiber optic probe, wherein the fiber optic probe comprises one or more optical fibers for directing laser light onto the tissue and for collecting light that is scattered by the tissue and guiding the collected light away from the tissue towards the signal detection unit, the fiber comprising a core, a cladding and optionally a coating, and
10 the fiber or fibers for collecting light having substantially no Raman signal in one or more parts of the 2500-3700 cm⁻¹ spectral region, and wherein the detection unit records the Raman signal scattered by the tissue in said spectral region.
- 15 26. Instrument according to claim 25, wherein the detection unit does substantially not measure fluorescence generated by other sources than the tissue.
27. Instrument according to claim 25 or 26, wherein the fiber optic probe comprises at least one fiber.
- 20 28. Instrument according to one of claims 25-27, wherein the fiber optic probe comprises at least one optical fiber having a fused silica core and a fused silica or Teflon or TECS cladding.
- 25 29. Instrument according to one of claims 25-28, by using a coating material in which intrinsically little or substantially no signal is generated in the 2500-3700 cm⁻¹ wavenumber interval.
- 30 30. Instrument according to one of claims 25-29, wherein the coating of the optical fiber comprises one or more of Teflon coatings and metal coatings.
31. Instrument according to one of claims 25-30, wherein the detection unit substantially measures only the signal obtainable from the core of the optic fiber.

WO 2004/051242

PCT/NL2003/000815

43

32. Instrument according to one of claims 25-31, wherein the laser light is only coupled into the central core of the fiber.
- 5 33. Instrument according to one of claims 25-32, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a laser light absorbing material.
- 10 34. Instrument according to one of claims 25-33, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a material having a higher refractive index than the first coating material.
- 15 35. Instrument for measuring a Raman signal of tissue according to one of claims 25-34, wherein the fiber optic probe comprises an optical fiber that both directs laser light onto the tissue and collects light that is scattered by the tissue and guides this collected light away from the tissue towards the signal detection unit, and wherein the fiber has substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
- 20 36. Instrument according to one of claims 25-35, wherein the detection unit also comprises a detector for measuring fluorescence and/or a detector for near-infrared absorption.
- 25 37. Instrument according to one of claims 25-36 wherein fluorescence and/or near-infrared absorption measurements make use of a fiber also used in obtaining Raman signal and wherein the detection unit also comprises a detector for measuring fluorescence and/or a detector for near-infrared absorption.
- 30 38. Instrument according to one of claims 25-37 wherein the fiber optic probe comprises a bundle of fibers for measuring and/or scanning a tissue area.

39. Instrument according to one of claims 25-38, wherein the fiber optic probe comprises one optical fiber, the fiber having substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
- 5 40. Instrument according to one of claims 25-39, wherein the optical fiber comprises a laser light absorbing end tip coating.
41. Instrument according to one of claims 25-40, wherein the end face of the optical fiber, where the laser light is coupled into the optical fiber, is polished.
- 10 42. A method for producing and measuring a Raman signal of tissue, comprising providing a laser, a detection unit for measuring a Raman signal, and a fiber optic probe, wherein the fiber optic probe comprises one or more optical fibers for directing laser light onto the tissue and for collecting light that is scattered by the tissue and guiding the collected light away from the tissue toward the signal
- 15 detection unit, the fiber comprising a core, a cladding and optionally a coating, sending laser light through the one or more optical fibers, receiving the Raman signal from the tissue through the one or more optical fibers and detecting the Raman signal by a signal detection unit, the fiber or fibers for collecting light
- 20 having substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region, and wherein the signal detection unit records the Raman signal in said spectral region.
43. Method according to claim 41, further comprising sending the laser light through a
- 25 same optical fiber which also receives the Raman signal, using an optical fiber for this method which has substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region
44. A method for measuring a Raman signal of a tissue sample, wherein an instrument
- 30 according to one of claims 25-41 is used and wherein the tissue sample is excised, biopted or taken from a human or animal body before measuring.

45. Method for evaluating an optical fiber for measuring a Raman signal of tissue, wherein an instrument according to one of claims 25-41 is used and wherein a tissue sample is excised, biopsied or taken from a human or animal body before measuring, and wherein the Raman signal of the optical fiber is measured of the sample and of a blanc, and wherein the Raman signals of the sample and of the blanc are compared.
46. Method for evaluating the suitability of a type of fiber for measuring the Raman signal of tissue, comprising:
- using an instrument according to one of claims 25-41
 - performing a measurement without tissue being present at the distal end of the fiber,
 - performing a measurement with tissue being present at the distal end of the fiber,
 - comparing the spectra obtained with and without tissue being present
 - concluding that the fiber is suitable for measuring the Raman signal of tissue.

Replaced by Act. 34

AMENDED CLAIMS

**[Received by the International Bureau on 10 May 2004 (10.05.04):
original claims 1-46 replaced by amended/new claims 1-44]**

1. Use of an instrument for measuring a Raman signal of tissue, the instrument comprising a laser, a signal detection unit for measuring the Raman signal, and a
5 fiber optic probe, wherein the fiber optic probe comprises one or more optical fibers for directing laser light onto the tissue and for collecting light that is scattered by the tissue and guiding the collected light away from the tissue towards the signal detection unit, the fiber comprising a core, a cladding and optionally a coating, and the fiber or fibers for collecting light having substantially no Raman signal in one
10 or more parts of the 2500-3700 cm^{-1} spectral region, and wherein the detection unit records the Raman signal scattered by the tissue in said spectral region, and wherein the fiber optic probe comprises an optical fiber that both directs laser light onto the tissue and collects light that is scattered by the tissue and guides the collected light away from the tissue towards the signal detection unit, and wherein the fiber has
15 substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
2. Use of an instrument according to claim 1, wherein the detection unit does substantially not measure fluorescence generated by other sources than the tissue.
20
3. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises at least one fiber having a low OH⁻ fused silica core.
4. Use of an instrument according to one of the preceding claims, wherein the fiber
25 optic probe comprises at least one optical fiber having a fused silica core and a fused silica or Teflon or TECS cladding.
5. Use of an instrument according to one of the preceding claims, by using a coating material in which intrinsically little or substantially no signal is generated in the
30 2500-3700 cm^{-1} wavenumber interval.

AMENDED SHEET (ARTICLE 19)

WO 2004/051242

47

PCT/NL2003/000815

6. Use of an instrument according to one of the preceding claims, wherein the coating of the optical fiber comprises one or more of Teflon coatings and metal coatings.
- 5 7. Use of an instrument according to one of the preceding claims, wherein the detection unit substantially measures only the signal obtainable from the core of the optic fiber.
- 10 8. Use of an instrument according to one of the preceding claims, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a laser light absorbing material.
- 15 9. Use of an instrument according to one of the preceding claims, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a material having a higher refractive index than the first coating material.
- 20 10. Use of an instrument according to one of the preceding claims, wherein the optical fiber comprises a laser light absorbing end tip coating.
11. Use of an instrument according to one of the preceding claims, wherein the detection unit records the Raman signal in one or more parts of the $2700-3100\text{ cm}^{-1}$ spectral region.
- 25 12. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises an optical element at the distal end of the optical fiber.
- 30 13. Use of an instrument according to one of the preceding claims, further comprising a signal analysis unit which analyses the recorded Raman signal, the analysis comprising an algorithm which outputs data regarding the molecular composition of the tissue and/or the clinical diagnostic class to which the tissue belongs.

AMENDED SHEET (ARTICLE 19)

14. Use of an instrument according to one of the preceding claims for analysis and/or diagnosis of atherosclerotic plaque.
15. Use of an instrument according to one of the preceding claims for use in the analysis and/or diagnosis of cancerous tissue or pre-cancerous tissue.
16. Use of an instrument according to one of the preceding claims for skin diagnosis.
17. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe is integrated or combined with a catheter.
18. Use of an instrument according to one of the preceding claims, wherein Raman measurements can be combined with fluorescence and/or near-infrared absorption measurements and wherein the detection unit also comprises a detection unit for measuring the intensity and/or spectrum of tissue fluorescence and/or a detection unit for measuring near-infrared absorption.
19. Use of an instrument according to claim 18, wherein fluorescence and/or near-infrared absorption measurements make use of a fiber also used in obtaining Raman signal.
20. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises a bundle of fibers for measuring and/or scanning a tissue area.
21. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe comprises one optical fiber, the fiber having substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
22. Use of an instrument according to one of the preceding claims, wherein the fiber optic probe is brought in, or in contact with, or in proximity to the tissue under investigation.

AMENDED SHEET (ARTICLE 19)

WO 2004/051242

49

PCT/NL2003/000815

23. Use of an instrument according to one of the preceding claims, wherein the tissue is excised, biopsied or taken from a human or animal body before measuring.
24. An instrument for measuring a Raman signal of tissue, the instrument comprising a
5 laser, a signal detection unit for measuring the Raman signal, and a fiber optic probe, wherein the fiber optic probe comprises one or more optical fibers for directing laser light onto the tissue and for collecting light that is scattered by the tissue and guiding the collected light away from the tissue towards the signal
10 detection unit, the fiber comprising a core, a cladding and optionally a coating, and the fiber or fibers for collecting light having substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region, and wherein the detection unit records the Raman signal scattered by the tissue in said spectral region, and wherein
15 the fiber optic probe comprises an optical fiber that both directs laser light onto the tissue and collects light that is scattered by the tissue and guides the collected light away from the tissue towards the signal detection unit, and wherein the fiber has substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
25. Instrument according to claim 24, wherein the detection unit does substantially not
20 measure fluorescence generated by other sources than the tissue.
26. Instrument according to claim 24 or 25, wherein the fiber optic probe comprises at least one fiber.
- 25 27. Instrument according to one of claims 24-26, wherein the fiber optic probe comprises at least one optical fiber having a fused silica core and a fused silica or Teflon or TECS cladding.
28. Instrument according to one of claims 24-27, by using a coating material in which
30 intrinsically little or substantially no signal is generated in the 2500-3700 cm^{-1} wavenumber interval.

AMENDED SHEET (ARTICLE 19)

WO 2004/051242

PCT/NL2003/000815

50

29. Instrument according to one of claims 24-28, wherein the coating of the optical fiber comprises one or more of Teflon coatings and metal coatings.
30. Instrument according to one of claims 24-29, wherein the detection unit substantially measures only the signal obtainable from the core of the optic fiber.
31. Instrument according to one of claims 24-30, wherein the laser light is only coupled into the central core of the fiber.
32. Instrument according to one of claims 24-31, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a laser light absorbing material.
33. Instrument according to one of claims 24-32, wherein the fiber comprises a first and a second coating, the first coating as coating on the cladding and the second coating as coating on the first coating, wherein the second coating comprises a material having a higher refractive index than the first coating material.
34. Instrument according to one of claims 24-33, wherein the detection unit also comprises a detector for measuring fluorescence and/or a detector for near-infrared absorption.
35. Instrument according to one of claims 24-34 wherein fluorescence and/or near-infrared absorption measurements make use of a fiber also used in obtaining Raman signal and wherein the detection unit also comprises a detector for measuring fluorescence and/or a detector for near-infrared absorption.
36. Instrument according to one of claims 24-35 wherein the fiber optic probe comprises a bundle of fibers for measuring and/or scanning a tissue area.

AMENDED SHEET (ARTICLE 19)

WO 2004/051242

51

PCT/NL2003/000815

37. Instrument according to one of claims 24-36, wherein the fiber optic probe comprises one optical fiber, the fiber having substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
- 5 38. Instrument according to one of claims 24-37, wherein the optical fiber comprises a laser light absorbing end tip coating.
39. Instrument according to one of claims 24-38, wherein the end face of the optical fiber, where the laser light is coupled into the optical fiber, is polished.
- 10 40. A method for producing and measuring a Raman signal of tissue, comprising providing a laser, a detection unit for measuring a Raman signal, and a fiber optic probe, wherein the fiber optic probe comprises one or more optical fibers for directing laser light onto the tissue and for collecting light that is scattered by the
- 15 tissue and guiding the collected light away from the tissue toward the signal detection unit, the fiber comprising a core, a cladding and optionally a coating, sending laser light through the one or more optical fibers, receiving the Raman signal from the tissue through the one or more optical fibers and detecting the Raman signal by a signal detection unit, the fiber or fibers for collecting light
- 20 having substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region, and wherein the signal detection unit records the Raman signal in said spectral region, and wherein the fiber optic probe comprises an optical fiber that both directs laser light onto the tissue and collects light that is scattered by the tissue and guides the collected light away from the tissue towards the signal
- 25 detection unit, and wherein the fiber has substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region.
41. Method according to claim 40, further comprising sending the laser light through a same optical fiber which also receives the Raman signal, using an optical fiber for
- 30 this method which has substantially no Raman signal in one or more parts of the 2500-3700 cm^{-1} spectral region

AMENDED SHEET (ARTICLE 19)

WO 2004/051242

52

PCT/NL2003/000815

42. A method for measuring a Raman signal of a tissue sample, wherein an instrument according to one of claims 24-39 is used and wherein the tissue sample is excised, biopted or taken from a human or animal body before measuring.

5 43. Method for evaluating an optical fiber for measuring a Raman signal of tissue, wherein an instrument according to one of claims 24-39 is used and wherein a tissue sample is excised, biopted or taken from a human or animal body before measuring, and wherein the Raman signal of the optical fiber is measured of the sample and of a blanc, and wherein the Raman signals of the sample and of the
10 blanc are compared.

44. Method for evaluating the suitability of a type of fiber for measuring the Raman signal of tissue, comprising:

- using an instrument according to one of claims 24-39
- 15 - performing a measurement without tissue being present at the distal end of the fiber,
- performing a measurement with tissue being present at the distal end of the fiber,
- comparing the spectra obtained with and without tissue being present
- concluding that the fiber is suitable for measuring the Raman signal of tissue.

AMENDED SHEET (ARTICLE 19)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.